



UB05-02-PSH-N01-B

- Specification
1. Current Rating 1.5AMP at 250AC
Voltage Rating:30V
 2. Insulation Resistance:1000M Min
 3. Contact Resistance:30mM Max
 4. Dielectric Withstanding Voltage:500V AC
 5. Temperature Range:-20°C to +85°C
 6. Mechanical Characteristics:
Insertion Force: 35 Newtons maximum
Extraction Force:8 Newtons minimum

MICRO 5P

MICRO 5P 从01到0.8款
胶芯颜色材质 (B:PBT黑, W: PBT白,
P:PA46黑, L:LCP灰)

外壳材质 (C:铜 S:不锈钢)

端子材质 (P:磷铜, H:黄铜)

外壳电镀 (N:镀镍 G:金 0:不电镀)

端子镀金厚度 (01:1U 03:3U 05:5U 15:15U 30:30U)

A: 外壳无倒刺 B: 带倒刺, C: 无倒刺短脚 (外壳流水号)

钻宝电子有限公司 Zuanbao Electronics Co., Ltd					
第三角投影 	图纸类型 成品图		图纸名称: MICRO-5P01		
	设计	产品名称 Micro 5P	产品编号		
审核	模具名称	模具编号			
批准	材质:	缩水: 仅供参考	版号: A/0	页数: 第 1 页 / 共 1 页	

未注线性公差: 未注角度公差:

X.X=±15 X=±1°

X.XX=±0.10 X.X=±0.5°

X.XXX=±0.05 X.XX=±0.1°