



PIN	TOLER.	Code	PART NUMBER
1.65	± 0.05	001	
2.00	± 0.05	002	
2.45	± 0.05	003	

No.	Name	QTY	Material	Plating
1	Pin	1	Brass	Ni:50u"
2	Break Contact	1	H62 Brass t=0.4	
3	Base	1	PBT+15%GF UL94V-0(Black)	
4	Tip Contact	1	QSn6.5-0.1 t=0.3	Ni(30u") Sn(80u")
5	Contact Needle	1	H62 Brass t=0.3	Ni(30u") Sn(80u")
6	Cover	1	PBT+15%GF UL94V-0(Black)	

- Technical requirement:
1. This product meets EU RoHS related requirement.
 2. The surface of plastic part should be without any crackle such as burr, lack, and so on phenomenon.
 3. The surface of metal part should be without any defect such as sacur, nick, oxidation and plating problem.
 4. The electronic performance should be the same as spec.
 5. The un-specified tolerance is : .X±0.25
.XX±0.15
.XXX±0.05

Previous Issue No.	
New Issue No.	
Date	
Signature	

Sign Number	Update	Signer	Date
Designer	Jiangqiang Chen	Standardization	Yaowu Zhao
Collate	Jian Gao	Approved	Xiufeng Bao
Verifier	Lixin Zhou		
Technology	Xianfu Zhou		
			2012.3.17

DC-022-04-XXX		AVK 8 3.665. 022	
DC POWER OUTLET			
Design Mark	Weight	Proportion	
A		3-1	
Total 1 Page	Page 1	ZUANBAO ELECTRONIC Co., Ltd.	